


Winter storage checklist for recreational vehicles



Step-by-step winter storage for your RV

- Drain and rinse the freshwater, grey water and black water tanks.
- Empty the water lines via the drains under the vehicle.
- Open the taps and operate the pump for complete drainage.
- Shut off the water-heater intake valve and adjust the bypass valves to winter setting.
- Turn off the heater's electrical switch and completely drain the hot-water tank.
- Remove the water filter and store it in a dry place.
- Pour antifreeze into the freshwater tank and the drains for the washbasin, bath, shower and toilet. Turn on the pump and open the taps until the antifreeze flows through.
- Empty and wash the refrigerator and leave the door ajar.
- Inspect the joints of the RV's roof, doors, windows and slideouts, and replace as required.
- Park the RV indoors.
- Submit a registration refund request to the SAAQ, together with the vehicle's registration certificate.

Step-by-step winter storage for your motorcycle or ATV

- Fill up the fuel tank.
- Inflate the tires to the recommended pressure.
- Clean the bodywork, tires and plastic surfaces.
- Grease the chain.
- Disconnect the battery and store it away from the cold.
- Park the vehicle indoors.
- Cover the vehicle with a breathable cover.
- Submit a registration refund request to the SAAQ, together with the vehicle's registration certificate.